



NO: RD-HA-SD071
DATE: 2005/09/15 I (REV:A1)

10/100 BASE-T SMT TRANSFORMER

MODEL NO.: HA-071

FEATURE:

RoHS Compliant

RoHS peak solder rating 260

Designed to meet IR requirement

Specifications @ 25



Operating temp. : -40 ~ +85

Part Number	OCL 100KHz 0.1Vrms 8mADC	HI-POT
HA-071	350uH MIN	1500VAC


SCHEMATICS:

DIMENSION: mm

TOLERANCE:±0.25(0.010)



Packing :



A-A SECTION

DIMENSION	W	P1	PO	E	F	AO	BO	Aot
SPEC.	24.0	16.0	4.0	1.75	11.5	10.0	13.2	0.08
+/-	0.30	0.10	0.10	0.10	0.10	0.10	0.10	(MIN)
DIMENSION	KO	P2	Do	D1	10Po	T	K1	Bot
SPEC.	6.80	2.0	1.55	1.5	40.0	0.40	6.15	0.08
+/-	0.10	0.10	0.05	(MIN)	0.20	0.10	0.10	(MIN)


Tape & reel.....600/reel
Tape.....39/tub



NO: RD-HA-SD071
DATE: 2005/09/15 I (REV:A1)

MODEL NO.: HA-071

Profile of IR Reflow (Lead Free)



PACKING

1. Tape & Reel : 600pcs / Reel , 3000pcs / Carton
2. Dry Pack : 1pcs
Product Description:(5g Silica Gel Desiccant)
PH: 4-8
Package Materials: Paper(Length 6.5±1cm , Width 5±1cm)
3. Reel Packed By Vocumm
4. Seal Per Jedec

